

# ALLTRAX INC

## CLUB CAR SERIES APPLICATION & CROSS REFERENCE GUIDE

Model / Year	Throttle	Identifiers	Stock* Controller	Mild* Performance	Wild* Performance	Extreme* Performance
95 & Older (All Pre 1994 cars, some 95, 96 year cars)	<b>0-5K</b>	Black Curtis controller w/ Black & White throttle wires	Flat Courses <b>SPM48200</b>  Hilly Courses <b>SPM48300</b>	<b>SPM48400</b> <b>SPM48500</b>	<b>SPM48500</b>  <b>SPM48600</b>	<b>SPM48800</b>
96 & Newer (Some 95 & 96 cars and all newer series cars)	<b>5K-0</b> <b>3 wire</b>	Silver or Black Curtis Controller w/ Green and yellow throttle wires	Flat Courses <b>SPM48200</b>  Hilly Courses <b>SPM48300</b>	<b>SPM48400</b> <b>SPM48500</b>	<b>SPM48500</b>  <b>SPM48600</b>	<b>SPM48800</b>
Performance upgrades – use correctly sized equipment. <b>See Technical Note #10 for more information</b>						

*\*Stock – No Upgrades; Mild – Big tires OR motor, but not both; Wild – Big Tires AND Motor or NEV's; Extreme – Hunting buggy, EV's and other high performance applications*



### SPM CABINET LENGTH


SPB48200 = 7" (179mm)  
 SPM48300 = 7" (179mm)  
 SPM48400 = 9" (229mm)  
 SPM48500 = 10" (254mm)  
 SPM48600 = 14" (356mm)  
 SPM48800 = 16" (407mm)

### FEATURES:



#### Color Coded Terminals

**Red:** B+ (Battery Pos)  
**Black:** B- (Battery Neg)  
**Blue:** M- (Motor Neg)  
**Green:** A2 (Plug Brake)  
 SPB Models Only



#### Flexi-Mount clip on tabs

- Active Main Solenoid Control
- Output Short Circuit Tolerant
- Higher Continuous Output Circuit
- Complete Thermal Solution –  
No external heatsink needed
- USB 2.0 Programming Port
- Support for 10 different throttles
- Made in the USA